

US-SDO221DL-TH / US-SDO421DL-TH

2MP/4MP WIFI Dual Light Speed Dome PTZ Camera with Temperature & Humidity Sensor



Product Features:

- 2MP (1920x1080) /4MP (2560×1440) high resolution
- Temperature & Humidity detection
- 6X digital Zoom
- 3.6mm lens
- 2inch mini housing
- Motion detection, Sound Detection, auto tracking
- Siren alarm
- TF card circulate recording video
- Two way audio
- Dual lights, 3 mode of Lighting (Day performance, infrared way, color night version)
- IP65 waterproof rating
- Pan 355 degree & Tilt 90degree

Specifications:

Resolution	1080P(1920*1280) ; 4MP(2560×1440)
Sensor	1/2.7 inch CMOS
Lens	3.6mm standard lens
Video Compress	H.264+
Zoom	Digital 6X
Pan/Tilt Angle	Level:355° , Tilt: 90°
Mini Sensitivity	0.02Lux
Infrared night vision	Dual led light, maximum support 15 meters
Frame	1080P@25FPS; 720P@25FPS
Video code stream	1080P: 1.2~1.5Mbps; 720P: 512Kbps
Audio format	G.711A
Support protocol	HTTP,HTTPS,TCP,IPV4,IPV6,UDP,RTSP,ICMP,RTP,DHCP,ARP,DNS,QoS
WiFi protocol	IEEE 802.11b/g/n
Image rotation	Mirror / inversion
Video control	Support
A two-way voice	Support
Motion detection	Support
Automatic tracking	Support
Sound detection	Support
Siren alarm	Support
Temperature & Humidity	Support
Alarm action	Email alarm sent/real-time alarm information push
Audio channel	Built-in MIC
TF storage	Max support 128G TF card
Cloud storage	Free 1 month cloud storage experience
Interface RJ45	One way to add camera
Interface Reset	Hardware Reset
Power supply	DC 12V 2A
Power waste	<24W
Power for white	DC 12V 0.6A
Lumen for white light	100LM
Working temperature	—20℃ ~ 60℃
Working humidity	10% ~ 80% no condensation